



## TIP35C



## NPN SILICON TRANSISTOR

### HIGH POWER TRANSISTORS

#### DESCRIPTION

The UTC **TIP35C** is a NPN Expitaxial-Base transistor, designed for using in general purpose amplifier and switching applications. Complement to TIP36C.

#### INTERNAL SCHEMATIC DIAGRAM



#### ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
TIP35CL-x-T3P-T	TIP35CG-x-T3P-T	TO-3P	B	C	E	Tube
TIP35CL-x-T3N-T	TIP35CG-x-T3N-T	TO-3PN	B	C	E	Tube

<p>TIP35CL-x-T3P-T</p> <ul style="list-style-type: none"> <li>(1) Packing Type</li> <li>(2) Package Type</li> <li>(3) Rank</li> <li>(4) Lead Plating</li> </ul>	<ul style="list-style-type: none"> <li>(1) T: Tube</li> <li>(2) T3P: TO-3P, T3N: TO-3PN</li> <li>(3) refer to Classification of <math>h_{FE1}</math></li> <li>(4) L: Lead Free, G: Halogen Free</li> </ul>
---	--

### ■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage ( $I_E = 0$ )	$V_{CBO}$	100	V
Collector-Emitter Voltage ( $I_B = 0$ )	$V_{CEO}$	100	V
Emitter-Base Voltage ( $I_C = 0$ )	$V_{EBO}$	5	V
Collector Current	$I_C$	25	A
Collector Peak Current	$I_{CM}$	50	A
Base Current	$I_B$	5	A
Total Dissipation ( $T_C = 25^\circ\text{C}$ )	$P_D$	125	W
Junction Temperature	$T_J$	+150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-65 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

### ■ THERMAL DATA

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Thermal Resistance Junction-Case	$\theta_{JC}$			1	$^\circ\text{C}/\text{W}$






### ■ ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-off Current ( $I_E = 0$ )	$I_{CBO}$	$V_{CB} = 100\text{ V}$			10	$\mu\text{A}$
Emitter Cut-off Current ( $I_C = 0$ )	$I_{EBO}$	$V_{EB} = 5\text{ V}$			10	$\mu\text{A}$
Collector-Emitter Sustaining Voltage ( $I_B = 0$ )	$V_{(BR)CEO}$	$I_C = 50\text{ mA}$	100			V
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_B = 1.5\text{ A}, I_C = 15\text{ A}$			1.8	V
		$I_B = 5\text{ A}, I_C = 25\text{ A}$			4	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = 5\text{ V}, I_C = 5\text{ A}$			1.5	V
DC Current Gain	$h_{FE1}$	$V_{CE} = 5\text{ V}, I_C = 1.5\text{ A}$	55		160	
	$h_{FE2}$	$V_{CE} = 4\text{ V}, I_C = 15\text{ A}$	15			
Transition Frequency	$f_T$	$V_{CE} = 5\text{ V}, I_C = 1\text{ A}$	3			MHz

### ■ CLASSIFICATION OF $h_{FE1}$

RANK	R	O
RANGE	55~110	80~160

### TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.